

LASER

ORDER CODE	DESCRIPTION	LIST PRICE
BATTERY-OPERATED LASER		
SPL-100	SPL-100 Laser level sensor, 98 ft. maximum measurement, wireless LoRa output, includes standard -20°F to 120°F (-30°F to 65°F) battery.	Call for price
SPL-100-C	SPL-100-C Laser level sensor, 98 ft. maximum measurement, wireless LoRa output, includes standard -40°F to 120°F (-40°F to 65°F) battery.	Call for price
FML-100	FML-100 Laser level sensor, 35 ft. maximum measurement, Wireless LoRa output, includes standard -20°F to 120°F battery. Must be used with FeedManager software.	Call for price
FML-100-C	FML-100-C Laser level sensor, 35 ft. maximum measurement, Wireless LoRa output, includes standard -40°F to 120°F battery. Must be used with FeedManager software.	Call for price
WIRELESS		
LM-100	LM-100 LoRa modem to receive wireless signal from SPL-100 or FML-100 laser level sensor and provide RS-485 output to BinInventory software. Power supply and NEMA 4X housing included.	Call for price
LG-100	LG-100 LoRa gateway to receive wireless signal from SPL-100 or FML-100 laser level sensor. Provides ethernet output to be utilized with BinView/FeedManager. Power supply and NEMA 4X housing included.	Call for price
LG-200	LG-100 LoRa gateway to receive wireless signal from SPL-100 or FML-100 laser level sensor. Provides Cellular (cellular plan to be purchased separately) output to be utilized with BinView/FeedManager. Power supply and housing included.	Call for price
530-0570	485 to USB converter	Call for price
344-0006	485 to Ethernet converter (TCP/IP)	Call for price
MOUNTING PLATES FOR BATTERY-OPERATED LASER		
SWVL-45	Swivel mount with 1.5" NPT female connector. Can swivel in one direction up to 45°.	Call for price
730-0298	GRMP-6 - 0° 1-1/2" NPT Powder coated carbon steel mounting plate with half coupling	Call for price
730-0501	GRMP-11 - 5° 1.5" NPT Powder coated carbon steel mounting plate with half coupling	Call for price
730-0502	GRMP-12 - 10° 1.5" NPT Powder coated carbon steel mounting plate with half coupling	Call for price
730-0633	GRMP-18 - 30° 1.5" NPT Powder coated carbon steel mounting plate with half coupling	Call for price
LASER LEVEL TRANSMITTER		
730-5176	LL-100 - Laser Level sensor, 1 ft to 160 ft (0.3 m to 50 m) range with 0.4 in (10 mm) resolution and +/- 1" (25 mm) accuracy. Non-visible laser beam with <1° beam angle. 12-28 VDC power input with 4 to 20 mA (3wire) output. Can be used in -4°F (-20°C) to 140°F (60°C) environments in an IP66 enclosure.	Call for price
MOUNTING PLATES		
258-0113	LL-900 Mounting Flange - ANSI (DN100 PN6/PN10) 4" 150# with <10° swivel angle.	Call for price
258-0114	LL-910 Mounting Flange - ANSI (DN65 PN6) 2.5" 150# with <10° swivel angle.	Call for price